
























**1 - 001 SINGLE CORE SILICONE CABLES FLEXIBLE AND SOLID**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C001 im:18	FG4/2		(SIF-SIAF-GS) CE	180°C	300/500V	COPPER FLEXIBLE	Class 5
CA01 im:4	EI2-FG4/2		(EI2 SIF - SIAF) CE	180°C	300/500V	COPPER FLEXIBLE	Class 5
CB01 im:4	AL-FG4/2		(K/FG4/2 - K/SIF) CE	180°C	300/500V	COPPER FLEXIBLE	Class 5
C002 im:14	UG4/2		(SID-SIA-SIR) CE	180°C	300/500V	COPPER SOLID	Class 1
CA02 im:4	UG4/2 - THT		(SID 250°C) CE	250°C	300/500V	COPPER SOLID	Class 1
CB02 im:2	AL-UG4/2		(K/UG4/2 - K/SID) CE	180°C	300/500V	COPPER SOLID	Class 1
C007 im:13	THT		(SIF 250°C-SIAF 250°C) CE	250°C	300/500V	COPPER FLEXIBLE	Class 5
C044 im:8	FG4/2 - HT		(SIF 220°C-SIAF 220°C) CE	220°C	300/500V	COPPER FLEXIBLE	Class 5
C045 im:7	FG4/300-E		(SIF 300V-SIAF 300V-GS 300V) CE	180°C	300V	COPPER FLEXIBLE	Class 5
C048 im:4	RG4/2-THT		CE	250°C	300/500V	COPPER SEMISOLID	Class 2
C051 im:1	H03S - K		CE 	180°C	300/300V	COPPER FLEXIBLE	Class 5
C052 im:17	H05S - K		CE 	180°C	300/500V	COPPER FLEXIBLE	Class 5
C053 im:18	H05S - U		CE 	180°C	300/500V	COPPER SOLID	Class 1
C071 im:10	N2GFAF		CE 	180°C	300/300V	COPPER FLEXIBLE	Class 5
C074 im:21	SIL/0100 F-Tin or Bare Copper		(N)2GFAF CE <VDE-REG >	180°C	300/300V	COPPER FLEXIBLE	Class 5
C072 im:10	N2GFA		CE 	180°C	300/300V	COPPER SOLID	Class 1
C075 im:8	SIL/0100 U		(N)2GFA CE <VDE-REG >	180°C	300/300V	COPPER SOLID	Class 1
C087 im:7	SIL/0400 F		CE <VDE-REG >	180°C	0.6/1 kV	COPPER FLEXIBLE	Class 5
C086 im:8	SIL/0500 F		<VDE-REG >	180°C	1.8/3 kV	COPPER FLEXIBLE	Class 5
C401 im:2	UL Style3136		CE 	150°C	300V	COPPER FLEXIBLE	UL Standard
C402 im:2	UL Style3099		CE 	150°C	300V	COPPER FLEXIBLE	UL Standard
C403 im:2	UL Style3099 VW-1		CE 	150°C	300V	COPPER FLEXIBLE	UL Standard
C404 im:3	UL Style3132 SIL		CE 	150°C	300V	COPPER FLEXIBLE	UL Standard
C405 im:3	UL Style3132 SIL VW1		CE 	150°C	300V	COPPER FLEXIBLE	UL Standard
C410 im:2	UL Style3123		CE 	150°C	600V	COPPER FLEXIBLE	UL Standard
C411 im:2	UL Style3123 VW-1		CE 	150°C	600V	COPPER FLEXIBLE	UL Standard
C412 im:2	UL Style3133		CE 	150°C	600V	COPPER FLEXIBLE	UL Standard
C413 im:2	UL Style3133 VW-1		CE 	150°C	600V	COPPER FLEXIBLE	UL Standard
C414 im:2	UL Style3134		CE 	150°C	600V	COPPER FLEXIBLE	UL Standard
C415 im:2	UL Style3134 VW-1		CE 	150°C	600V	COPPER FLEXIBLE	UL Standard
C421 im:2	UL Style3367		CE 	200°C	300V	COPPER FLEXIBLE	UL Standard
C422 im:3	UL Style3367 VW-1		CE 	200°C	300V	COPPER FLEXIBLE	UL Standard
C425 im:2	UL Style3135 Flex		CE 	200°C	600V	COPPER FLEXIBLE	UL Standard
C426 im:2	UL Style3135 Flex VW-1		CE 	200°C	600V	COPPER FLEXIBLE	UL Standard
C427 im:1	UL Style3135 Solid		CE 	200°C	600V	COPPER SOLID	UL Standard
C428 im:1	UL Style3135 Solid VW-1		CE 	200°C	600V	COPPER SOLID	UL Standard
C434 im:2	UL Style 3572 Flex		CE 	200°C	1000V	COPPER FLEXIBLE	UL Standard
C435 im:1	UL Style 3572 Solid		CE 	200°C	1000V	COPPER SOLID	UL Standard

**2 - 002 SINGLE CORE SILICONE/FIBERGLASS CABLES FLEXIBLE AND SOLID**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C003 im:17	FG4T2/2 Glass or Polyester (SIF/GL-SIAF/GL-GSV)	CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
CA03 im:7	FG4T2/2-Ni Glass or Polyester	CE		200°C	300/500V	NIKEL	
CB03 im:0	RG4T2/2 - AWG	CE		200°C	300/500V	COPPER FLEXIBLE	UL Standard
C004 im:12	UG4T2/2 Glass or Polyester (SID/GL-SIA/GL-SIR/GL)	CE		200°C	300/500V	COPPER SOLID	Class 1
C006 im:17	FG4T2/12	CE		200°C	600V	COPPER FLEXIBLE	Class 5
C008 im:14	THT/VT (SIF/GL 250°C-SIAF/GL 250°C)	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
C009 im:13	FG4T2/12-THT	CE		250°C	600V	COPPER FLEXIBLE	Class 5
C030 im:10	THT/VT-Ni	CE		250°C	300/500V	NIKEL	
C043 im:8	FG4T2/2-HT (SIF/GL 220°C-SIAF/GL 220°C)	CE		220°C	300/500V	COPPER FLEXIBLE	Class 5
C046 im:8	FG4T2/300-E Glass or Polyester (300V SIF/GL-SIAF/GL)	CE		200°C	300V	COPPER FLEXIBLE	Class 5
C047 im:6	FG4T2/2-R Glass or Polyester	CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
CA51 im:15	H05SJ - K	CE	IMQ HAR	180°C	300/500V	COPPER FLEXIBLE	Class 5
CA59 im:7	H05SJ - U	CE	IMQ HAR	180°C	300/500V	COPPER SOLID	Class 1
C059 im:14	UG4T2	CE	UL	180°C	300/500V	COPPER SOLID	Class 1
C060 im:14	UG4T2-T200°C	CE	UL	200°C	300/300V	COPPER SOLID	Class 1
C062 im:13	RG4T2-T200°C	CE	UL	200°C	300/300V	COPPER FLEXIBLE	UL Standard
C084 im:9	SIL/0100 F-T2- Tin or Bare Copper	CE	<VDE-REG >	180°C	300/300V	COPPER FLEXIBLE	Class 5
C085 im:10	SIL/0100 U-T2	CE	<VDE-REG >	180°C	300/300V	COPPER SOLID	Class 1
C406 im:2	UL Style3132 SIL/VT	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C407 im:2	UL Style3132 SIL/VT VW-1	CE	UL VW-1	150°C	300V	COPPER FLEXIBLE	UL Standard
C408 im:2	UL Style3068	CE	UL	150°C	300V	COPPER FLEXIBLE	UL Standard
C409 im:2	UL Style3068 VW-1	CE	UL VW-1	150°C	300V	COPPER FLEXIBLE	UL Standard
C416 im:2	UL Style3069	CE	UL	150°C	600V	COPPER FLEXIBLE	UL Standard
C417 im:2	UL Style3069 VW-1	CE	UL VW-1	150°C	600V	COPPER FLEXIBLE	UL Standard
C418 im:2	UL Style3070	CE	UL	150°C	600V	COPPER FLEXIBLE	UL Standard
C419 im:2	UL Style3070 VW-1	CE	UL VW-1	150°C	600V	COPPER FLEXIBLE	UL Standard
C420 im:2	UL Style3301	CE	UL	150°C	600V	COPPER FLEXIBLE	UL Standard
C423 im:1	UL Style3122	CE	UL	200°C	300V	COPPER FLEXIBLE	UL Standard
C424 im:1	UL Style3122 VW-1	CE	UL VW-1	200°C	300V	COPPER FLEXIBLE	UL Standard
C429 im:2	UL Style3071	CE	UL	200°C	600V	COPPER FLEXIBLE	UL Standard
C430 im:2	UL Style3071 VW-1	CE	UL VW-1	200°C	600V	COPPER FLEXIBLE	UL Standard
C431 im:1	UL Style3172	CE	UL	200°C	600V	COPPER FLEXIBLE	UL Standard
C432 im:1	UL Style3172 VW-1	CE	UL VW-1	200°C	600V	COPPER FLEXIBLE	UL Standard
C433 im:2	UL Style3144	CE	UL	200°C	600V	COPPER FLEXIBLE	UL Standard
C436 im:1	UL Style3067 ALLOY CONDUCTOR	CE	UL	200°C	600V	ALLOY	
C437 im:1	UL Style3067 ALLOY CONDUCTOR VW-1	CE	UL VW-1	200°C	600V	ALLOY	
C438 im:1	UL Style3076 ALLOY CONDUCTOR	CE	UL	150°C	300V	ALLOY	
C439 im:1	UL Style3076 ALLOY CONDUCTOR VW-1	CE	UL VW-1	150°C	300V	ALLOY	

**3 - 007 SINGLE CORE SIL.OR SIL./GLASS CABLES DOUBLE INSULATION**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
CA52 im:9	H05S - K (D.I.)	CE	IMQ HAR	180°C	300/500V	COPPER FLEXIBLE	Class 5
CA53 im:1	H05S-U (D.I.)	CE	IMQ HAR	180°C	300/500V	COPPER SOLID	Class 1
C055 im:14	FG4G4 450/750 V	CE	CEC	180°C	450/750V	COPPER FLEXIBLE	Class 5
C057 im:16	UG4G4 450/750 V	CE	CEC	180°C	450/750V	COPPER SOLID	Class 1
C056 im:15	FG4G4T2 450/750 V	CE	CEC	180°C	450/750V	COPPER FLEXIBLE	Class 5
C058 im:17	UG4G4T2 450/750 V	CE	CEC	180°C	450/750V	COPPER SOLID	Class 1
C077 im:13	SILHSiL F	CE	<VDE-REG>	180°C	300/300V	COPPER FLEXIBLE	Class 5
C078 im:14	SilHSil F-T2	CE	<VDE-REG>	180°C	300/500V	COPPER FLEXIBLE	Class 5
C079 im:13	SILHSiL U	CE	<VDE-REG>	180°C	300/300V	COPPER SOLID	Class 1
C080 im:15	SilHSil U-T2	CE	<VDE-REG>	180°C	300/500V	COPPER SOLID	Class 1

**4 - 005 NEON CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C041 im:12	NEON CABLES SILICONE EN50143 Several Variants		IMQ HAR	180°C	5000/10000V	COPPER FLEXIBLE	Class 5
C042 im:7	NEON CABLES PVC EN50143 Several Variants		IMQ HAR	70°C	5000/10000V	COPPER FLEXIBLE	Class 5

**5 - 003 SINGLE CORE GLASS/GLASS CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C015 im:4	VHT/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C016 im:14	VH/GR.2/RR	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
C017 im:18	VH/GR.2/Ni	CE		300°C	300/300V	NIKEL	
C018 im:12	VH//GR.2/R.Ni	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
C020 im:11	VH-IT/2G/Ni	CE		300°C	300/500V	NIKEL	
CA20 im:2	VH-IT/2G/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C032 im:9	VHIT/GR.2/Ni	CE		300°C	300/500V	NIKEL	
C033 im:10	VHIT/GR.2/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C036 im:9	VHIT/GR.2 Several Variants	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5

**6 - 004 SINGLE CORE PTFE/GLASS CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C010 im:15	VTC/RR	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
C011 im:16	VTC/Ni	CE		300°C	300/300V	NIKEL	
C012 im:14	VTC/R.Ni	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
C013 im:8	V2TC/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C014 im:7	V2TC/RR V2TC/RST	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
CA14 im:2	VTR/Ni	CE		300°C	300/300V	NIKEL	
C021 im:8	VTC/Ni - 1T	CE		300°C	300/300V	NIKEL	
C022 im:2	VTC/R.Ni-1T	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
C031 im:11	TSVVR Several Variants	CE		300°C	300/500V	NIKEL	
C037 im:6	TSVR-Ni	CE		250°C	300/300V	NIKEL	

<b>C038</b>	im:4	TSVVR Several Variants	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
-------------	------	------------------------	----	--	-------	----------	-----------------	---------

**7 - 010 SINGLE CORE CABLES-SPECIAL CONSTR.**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C034</b>	im:6 TS Several Variants	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C035</b>	im:5 TS/Ni	CE		250°C	300/500V	NIKEL	
<b>C300</b>	im:3 VH - RR - FRENI			250°C	48V	COPPER FLEXIBLE	Class 5
<b>C301</b>	im:6 FT2G4T2			200°C	48V	COPPER FLEXIBLE	Class 5

**8 - 006 VARIOUS CABLES WITH PVC INSULATION**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C261</b>	im:10 FRDR - FR 300/500 - FR3 HT	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C262</b>	im:5 FROR CC	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5

**9 - 011 MULTICORE SILICONE/SILICONE CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C023</b>	im:18 FG4OG4/2 Several Variants with or without armou	(SIHF) CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA23</b>	im:3 FG4OG4/2 S - Several Variants with shielding	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CB23</b>	im:1 FG4OG4/2 G-T200 FG4OG4/2 X-T200 FG4OG4/2 CC-T200	CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C024</b>	im:13 FG4OG4T2/2 Several Variants	(SIHF/GL) CE		200°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C028</b>	im:11 FG4W 180 or 250°C	(SIFZ-w) CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
<b>CA28</b>	im:2 UG4W	(SIDZ-w) CE		180°C	300/500V	COPPER SOLID	Class 1
<b>C029</b>	im:7 FG4WT2-THT/Ni	CE		250°C	300/300V	NIKEL	
<b>C303</b>	im:11 SIHF G	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C063</b>	im:15 H05SS-F Several Variants	CE	IMQ HAR	180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA63</b>	im:9 H05SSD3-K H05SSD3T-K Several Variants	CE	IMQ HAR	180°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CB63</b>	im:6 H05SS-F G (VM)	CE	IMQ HAR	180°C	300/500V	COPPER EXTRA-FLEX.	Class 6
<b>CA64</b>	im:6 UG4OG4 Several Variants	CE	CE	180°C	300/500V	COPPER SOLID	Class 1
<b>C175</b>	im:1 cUL MULTICONDUCTOR CABLE 150-300	CE	RU	150°C	300V	COPPER FLEXIBLE	UL Standard
<b>C176</b>	im:0 cUL MULTICONDUCTOR CABLE 200-300	CE	RU	200°C	300V	COPPER FLEXIBLE	UL Standard
<b>C451</b>	im:3 UL Style 4389 150-600	CE	RU US	150°C	600V	COPPER FLEXIBLE	UL Standard
<b>C452</b>	im:3 UL Style 4389 200-600	CE	RU US	200°C	600V	COPPER FLEXIBLE	UL Standard

**10 - 012 MULTICORE SILICONE/PVC CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
<b>C302</b>	im:7 EI2-SiF-PV/P(f)			90°C	48V	COPPER FLEXIBLE	Class 5
<b>C305</b>	im:5 EI2-SiF-PV/P(E)	CE		90°C	48V	COPPER FLEXIBLE	Class 5
<b>C304</b>	im:8 SIHF-PV G	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C054</b>	im:20 FG4OR Several Variants	CE	CE	90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>CA54</b>	im:5 FG4ORY Several Variants	CE	CE	90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C061</b>	im:14 FG4DR	CE	CE	90°C	300/500V	COPPER FLEXIBLE	Class 5
<b>C064</b>	im:10 UG4OR Several Variants	CE	CE	90°C	300/500V	COPPER SOLID	Class 1
<b>C076</b>	im:19 SILHYW (fl)	CE	<VDE-REG >	90°C	300/300V	COPPER FLEXIBLE	Class 5

<b>C081</b>	im:18	SiLHYW(rd) Several Variants	CE	<VDE-REG >	90°C	300/300V	COPPER FLEXIBLE	Class 5
<b>CA81</b>	im:8	SiLHYW(rd) G (VM)	CE	<VDE-REG >	90°C	300/300V	COPPER EXTRA-FLEX.	Class 6
<b>C082</b>	im:16	SiMHYW Several Variants	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5

**11 - 015 MULTICORE CABLES-SPECIAL CONSTR.**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
<b>C019</b>	im:16 VHO-A Several Variants	CE		250°C	300/300V	COPPER FLEXIBLE Class 5
<b>CA19</b>	im:1 VHTO-A R.Ni	CE		270°C	300/500V	---
<b>C025</b>	im:10 FG4OT2/2 G	CE		200°C	300/300V	COPPER FLEXIBLE Class 5
<b>C313</b>	im:1 FG4OG4/2-PS (SiHF/C)	CE		180°C	300/500V	COPPER FLEXIBLE Class 5

**12 - 022 MULTICORE CABLE WITH HELICOIDAL ASSEMBLY**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
<b>C308</b>	im:0 PVC D.I./RY - PVC D.I./PE	CE		70°C	300/500V	COPPER FLEXIBLE Class 5
<b>C309</b>	im:1 PVC/RY - PVC/PE	CE		70°C	300/500V	COPPER FLEXIBLE Class 5
<b>C310</b>	im:3 FG4TX/2-RY FG4TX/2-PE	CE		180°C	300/500V	COPPER FLEXIBLE Class 5
<b>C311</b>	im:2 FG4T2X/2-RY	CE		180°C	300/500V	COPPER FLEXIBLE Class 5
<b>C312</b>	im:0 FG4TX D.I. - PE	CE		180°C	300/500V	COPPER FLEXIBLE Class 5

**13 - 016 SPECIAL PRODUCTS**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
<b>C026</b>	im:14 SVFR			500°C		IRON-ALLUMINIUM-INOX etc.
<b>C027</b>	im:9 CORDONETTI			200°C		SUPPORT

**14 - 017 THERMOREGULATION CABLES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
<b>C221</b>	im:6 FRDR-T			70°C	48V	ALLOY
<b>C222</b>	im:7 FRDR-TA			70°C	48V	ALLOY
<b>C223</b>	im:6 FROPSR-T			70°C	48V	ALLOY
<b>C224</b>	im:6 FROASR-T			70°C	48V	ALLOY
<b>C225</b>	im:4 FROR-TA			70°C	48V	ALLOY
<b>C226</b>	im:5 FROR-T			70°C	48V	ALLOY
<b>C231</b>	im:21 VHDT2 Several Variants			250°C	48V	ALLOY
<b>C232</b>	im:16 VHOT2-T Several Variants			250°C	48V	ALLOY
<b>C233</b>	im:14 VHOT2-TR Several Variants		(PT 100)	250°C	48V	COPPER FLEXIBLE Class 5
<b>C241</b>	im:8 FG5O-TS UG5O-TS			250°C	48V	ALLOY
<b>C251</b>	im:11 FG4OG4-T			180°C	48V	ALLOY
<b>C252</b>	im:5 FG4OG4-TA			180°C	48V	ALLOY
<b>C253</b>	im:8 FG4OASG4-T			180°C	48V	ALLOY
<b>C254</b>	im:8 FG4OG4-TS			180°C	48V	ALLOY

**15 - 018 PROTECTION AND INSULATION SLEEVES**

Spec.	Product Name	CE	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
<b>C101</b>	im:9 G.801			250°C	---	---

<b>C102</b>	im:11	G.810/N - G.830/SIL - G.840/SIL/CAR			180°C	---
<b>C103</b>	im:9	G.600			180°C	---
<b>C105</b>	im:7	G810/S			250°C	---
<b>C106</b>	im:3	G.810/R			250°C	---
<b>C107</b>	im:1	G.600R			150°C	---
<b>C104</b>	im:13	TS1801 (kV 1,50 - 2,50 - 4,00)			200°C	---

**16 - 031 MONOTUBES FOR STEAM IRON SYSTEMS**

<u>Spec.</u>	<u>Product Name</u>	<u>CE</u>	<u>Homolog.</u>	<u>Temperature Range (°C)</u>	<u>Working Voltage</u>	<u>Conductor Type</u>
<b>C801</b> im:8	MONOTUBO con cavo VDE SIL/PVC	CE		90°C	300/300V	COPPER FLEXIBLE Class 5
<b>C805</b> im:9	MONOTUBO con cavo HAR SILICONE	CE		180°C	300/500V	COPPER FLEXIBLE Class 5
<b>C806</b> im:3	MONOTUBO con cavo SPECIALE SILICONE	CE		180°C	300/300V	COPPER EXTRA-FLEX. Class 6
<b>C815</b> im:8	MONOTUBO con cavo HAR H05RR-F o H05BB-F	CE		90°C	300/500V	---

**17 - 030 STEAM TUBES**

<u>Spec.</u>	<u>Product Name</u>	<u>CE</u>	<u>Homolog.</u>	<u>Temperature Range (°C)</u>	<u>Working Voltage</u>	<u>Conductor Type</u>
<b>C851</b> im:9	Tubo EPDM RIVESTITO	CE		130°C	---	---
<b>C852</b> im:5	Tubo EPDM	CE		130°C	---	---
<b>C853</b> im:1	Tubo SILICONE NON RIVESTITO	CE		250°C	---	---

**32 - S14 VARIOUS CABLES WITH PVC INSULATION**

<u>Spec.</u>	<u>Product Name</u>	<u>CE</u>	<u>Homolog.</u>	<u>Temperature Range (°C)</u>	<u>Working Voltage</u>	<u>Conductor Type</u>
<b>C307</b> im:0	B03VV-F-T/RY - B03VV-F-T/PE	CE		70°C	300/300V	COPPER FLEXIBLE Class 5