1 - 001 SINGLE CORE SILICONE CABLES FLEXIBLE AND SOLID

Spec.		Product Name		CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C001	im:19	FG4/2	*(SIF-SIAF-GS)*	CE UKCA		180°C	300/500V	COPPER FLEXIBLE	Class 5
CA01	im:4	EI2-FG4/2	*(EI2 SIF - SIAF)*	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
CB01	im:4	AL-FG4/2	*(K/FG4/2 - K/SIF)*	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
C002	im:15	UG4/2	*(SID-SIA-SIR)*	CE UKCA		180°C	300/500V	COPPER SOLID	Class 1
CA02	im:5	UG4/2 - THT	*(SID 250°C)*	CE UKCA		250°C	300/500V	COPPER SOLID	Class 1
CB02	im:2	AL-UG4/2	*(K/UG4/2 - K/SID)*	CE		180°C	300/500V	COPPER SOLID	Class 1
C007	im:14	THT	*(SIF 250°C-SIAF 250°C)*	CE UKCA		250°C	300/500V	COPPER FLEXIBLE	Class 5
C044	im:8	FG4/2 - HT	*(SIF 220°C-SIAF 220°C)*	CE		220°C	300/500V	COPPER FLEXIBLE	Class 5
C045	im:7	FG4/300-E	*(SIF 300V-SIAF 300V-GS 300V)*	CE		180°C	300V	COPPER FLEXIBLE	Class 5
C048	im:4	RG4/2-THT		CE		250°C	300/500V	COPPER SEMISOLID	Class 2
C051	im:2	H03S - K		CE UKCA	IMQ HAR	180°C	300/300V	COPPER FLEXIBLE	Class 5
C052	im:17	H05S - K		CE	IMQ HAR	180°C	300/500V	COPPER FLEXIBLE	Class 5
C053	im:18	H05S - U		CE	IMQ HAR	180°C	300/500V	COPPER SOLID	Class 1
C071	im:10	N2GFAF		CE	VDE	180°C	300/300V	COPPER FLEXIBLE	Class 5
C074	im:21	SIL/0100 F-Tin or Bare Copper	*(N)2GFAF*	CE	◁ VDE-REG ▷	180°C	300/300V	COPPER FLEXIBLE	Class 5
C072	im:10	N2GFA		CE	VDE	180°C	300/300V	COPPER SOLID	Class 1
C075	im:8	SIL/0100 U	*(N)2GFA*	CE	◁ VDE-REG ▷	180°C	300/300V	COPPER SOLID	Class 1
C087	im:8	SIL/0400 F		CE UKCA	◁ VDE-REG ▷	180°C	0.6/1 kV	COPPER FLEXIBLE	Class 5
C086	im:8	SIL/0500 F			◁ VDE-REG ▷	180°C	1.8/3 kV	COPPER FLEXIBLE	Class 5
C401	im:2	UL Style3136		CE	cULus	150°C	300V	COPPER FLEXIBLE	UL Standard
C402	im:2	UL Style3099		CE	cULus	150°C	300V	COPPER FLEXIBLE	UL Standard
C403	im:2	UL Style3099 VW-1		CE	cULus VW-1	150°C	300V	COPPER FLEXIBLE	UL Standard
C404	im:4	UL Style3132 SIL		CE	cULus	150°C	300V	COPPER FLEXIBLE	UL Standard
C405	im:3	UL Style3132 SIL VW1		CE	cULus VW-1	150°C	300V	COPPER FLEXIBLE	UL Standard
C410	im:2	UL Style3123		CE	cULus	150°C	600V	COPPER FLEXIBLE	UL Standard
C411	im:2	UL Style3123 VW-1		CE	cULus VW-1	150°C	600V	COPPER FLEXIBLE	UL Standard
C412	im:2	UL Style3133		CE	cULus	150°C	600V	COPPER FLEXIBLE	UL Standard
C413	im:2	UL Style3133 VW-1		CE	cULus VW-1	150°C	600V	COPPER FLEXIBLE	UL Standard
C414	im:2	UL Style3134		CE	cULus	150°C	600V	COPPER FLEXIBLE	UL Standard
C415	im:2	UL Style3134 VW-1		CE	cULus VW-1	150°C	600V	COPPER FLEXIBLE	UL Standard
C421	im:2	UL Style3367		CE	cULus	200°C	300V	COPPER FLEXIBLE	UL Standard
C422	im:4	UL Style3367 VW-1		CE	cULus VW-1	200°C	300V	COPPER FLEXIBLE	UL Standard
C425	im:3	UL Style3135 Flex		CE UKCA	cULus	200°C	600V	COPPER FLEXIBLE	UL Standard
C426	im:3	UL Style3135 Flex VW-1		CE UKCA	cULus VW-1	200°C	600V	COPPER FLEXIBLE	UL Standard
C427	im:1	UL Style3135 Solid		CE	cULus	200°C	600V	COPPER SOLID	UL Standard
C428	im:1	UL Style3135 Solid VW-1		CE	cULus VW-1	200°C	600V	COPPER SOLID	UL Standard
C434	im:2	UL Style 3572 Flex		CE	cULus	200°C	1000V	COPPER FLEXIBLE	UL Standard

C435	im:1	UL Style 3572 Solid			200°C	1000V	COPPER SOLID	UL Standard

2 - 002 SINGLE CORE SILICONE/FIBERGLASS CABLES FLEXIBLE AND SOLID

Spec.		Product Name		CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C003	im:18	FG4T2/2 Glass or Polyester	*(SIF/GL-SIAF/GL-GSV)*			200°C	300/500V	COPPER FLEXIBLE	Class 5
CA03	im:7	FG4T2/2-Ni Glass or Polyester				200°C	300/500V	NIKEL	
CB03	im:0	RG4T2/2 - AWG				200°C	300/500V	COPPER FLEXIBLE	UL Standard
C004	im:13	UG4T2/2 Glass or Polyester	*(SID/GL-SIA/GL-SIR/GL)*			200°C	300/500V	COPPER SOLID	Class 1
C006	im:17	FG4T2/12				200°C	600V	COPPER FLEXIBLE	Class 5
C008	im:14	THT/VT	*(SIF/GL 250°C-SIAF/GL 250°C)*			250°C	300/500V	COPPER FLEXIBLE	Class 5
C009	im:14	FG4T2/12-THT				250°C	600V	COPPER FLEXIBLE	Class 5
C030	im:10	THT/VT-Ni				250°C	300/500V	NIKEL	
C043	im:9	FG4T2/2-HT	*(SIF/GL 220°C-SIAF/GL 220°C)*			220°C	300/500V	COPPER FLEXIBLE	Class 5
C046	im:8	FG4T2/300-E Glass or Polyester	*(300V SIF/GL-SIAF/GL)*			200°C	300V	COPPER FLEXIBLE	Class 5
C047	im:6	FG4T2/2-R Glass or Polyester				200°C	300/500V	COPPER FLEXIBLE	Class 5
CA51	im:17	H05SJ - K				180°C	300/500V	COPPER FLEXIBLE	Class 5
CA59	im:7	H05SJ - U				180°C	300/500V	COPPER SOLID	Class 1
C059	im:14	UG4T2				180°C	300/500V	COPPER SOLID	Class 1
C060	im:14	UG4T2-T200°C				200°C	300/300V	COPPER SOLID	Class 1
C062	im:13	RG4T2-T200°C				200°C	300/300V	COPPER FLEXIBLE	UL Standard
C084	im:9	SIL/0100 F-T2- Tin or Bare Copper			◁ VDE-REG ▷	180°C	300/300V	COPPER FLEXIBLE	Class 5
C085	im:11	SIL/0100 U-T2			◁ VDE-REG ▷	180°C	300/300V	COPPER SOLID	Class 1
C406	im:2	UL Style3132 SIL/VT				150°C	300V	COPPER FLEXIBLE	UL Standard
C407	im:2	UL Style3132 SIL/VT VW-1				150°C	300V	COPPER FLEXIBLE	UL Standard
C408	im:2	UL Style3068				150°C	300V	COPPER FLEXIBLE	UL Standard
C409	im:2	UL Style3068 VW-1				150°C	300V	COPPER FLEXIBLE	UL Standard
C416	im:2	UL Style3069				150°C	600V	COPPER FLEXIBLE	UL Standard
C417	im:2	UL Style3069 VW-1				150°C	600V	COPPER FLEXIBLE	UL Standard
C418	im:2	UL Style3070				150°C	600V	COPPER FLEXIBLE	UL Standard
C419	im:2	UL Style3070 VW-1				150°C	600V	COPPER FLEXIBLE	UL Standard
C420	im:2	UL Style3301				150°C	600V	COPPER FLEXIBLE	UL Standard
C423	im:1	UL Style3122				200°C	300V	COPPER FLEXIBLE	UL Standard
C424	im:1	UL Style3122 VW-1				200°C	300V	COPPER FLEXIBLE	UL Standard
C429	im:2	UL Style3071				200°C	600V	COPPER FLEXIBLE	UL Standard
C430	im:2	UL Style3071 VW-1				200°C	600V	COPPER FLEXIBLE	UL Standard
C431	im:1	UL Style3172				200°C	600V	COPPER FLEXIBLE	UL Standard
C432	im:1	UL Style3172 VW-1				200°C	600V	COPPER FLEXIBLE	UL Standard
C433	im:2	UL Style3144				200°C	600V	COPPER FLEXIBLE	UL Standard
C436	im:1	UL Style3067 ALLOY CONDUCTOR				200°C	600V	ALLOY	
C437	im:1	UL Style3067 ALLOY CONDUCTOR VW-1				200°C	600V	ALLOY	

C438	im:1	UL Style3076 ALLOY CONDUCTOR	CE	cULus	150°C	300V	ALLOY
C439	im:1	UL Style3076 ALLOY CONDUCTOR VW-1	CE	cULus VW-1	150°C	300V	ALLOY

3 - 007 SINGLE CORE SIL.OR SIL./GLASS CABLES DOUBLE INSULATION

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
CA52	im:10	H05S - K (D.I.)	CE UKCA	IMQ HAR	180°C	300/500V	COPPER FLEXIBLE	Class 5
CA53	im:1	H05S-U (D.I.)	CE	IMQ HAR	180°C	300/500V	COPPER SOLID	Class 1
C055	im:15	FG4G4 450/750 V	CE UKCA		180°C	450/750V	COPPER FLEXIBLE	Class 5
C057	im:17	UG4G4 450/750 V	CE UKCA		180°C	450/750V	COPPER SOLID	Class 1
C056	im:15	FG4G4T2 450/750 V	CE		180°C	450/750V	COPPER FLEXIBLE	Class 5
C058	im:17	UG4G4T2 450/750 V	CE		180°C	450/750V	COPPER SOLID	Class 1
C077	im:14	SiLHSiL F	CE UKCA	◁ VDE-REG ▷	180°C	300/300V	COPPER FLEXIBLE	Class 5
C078	im:14	SilHSil F-T2	CE	◁ VDE-REG ▷	180°C	300/500V	COPPER FLEXIBLE	Class 5
C079	im:14	SiLHSiL U	CE UKCA	◁ VDE-REG ▷	180°C	300/300V	COPPER SOLID	Class 1
C080	im:15	SilHSil U-T2	CE	◁ VDE-REG ▷	180°C	300/500V	COPPER SOLID	Class 1

4 - 005 NEON CABLES

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C041	im:12	NEON CABLES SILICONE EN50143 Several Variants		IMQ HAR	180°C	5000/10000V	COPPER FLEXIBLE	Class 5
C042	im:7	NEON CABLES PVC EN50143 Severl Variants		IMQ HAR	70°C	5000/10000V	COPPER FLEXIBLE	Class 5

5 - 003 SINGLE CORE GLASS/GLASS CABLES

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C015	im:4	VHT/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C016	im:14	VH/GR.2/RR	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
C017	im:18	VH/GR.2/Ni	CE		300°C	300/300V	NIKEL	
C018	im:12	VH//GR.2/R.Ni	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
C020	im:11	VH-IT/2G/Ni	CE		300°C	300/500V	NIKEL	
CA20	im:2	VH-IT/2G/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C032	im:9	VHIT/GR.2/Ni	CE		300°C	300/500V	NIKEL	
C033	im:10	VHIT/GR.2/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C036	im:9	VHIT/GR.2 Several Variants	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5

6 - 004 SINGLE CORE PTFE/GLASS CABLES

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C010	im:15	VTC/RR	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
C011	im:17	VTC/Ni	CE UKCA		300°C	300/300V	NIKEL	
C012	im:14	VTC/R.Ni	CE		270°C	300/300V	COPPER FLEXIBLE	Class 5
C013	im:8	V2TC/R.Ni	CE		270°C	300/500V	COPPER FLEXIBLE	Class 5
C014	im:7	V2TC/RR V2TC/RST	CE		250°C	300/500V	COPPER FLEXIBLE	Class 5
CA14	im:2	VTR/Ni	CE		300°C	300/300V	NIKEL	
C021	im:8	VTC/Ni - 1T	CE		300°C	300/300V	NIKEL	

C022	im:3	VTC/R.Ni-1T			270°C	300/300V	COPPER FLEXIBLE	Class 5
C031	im:11	TSVVR Several Variants			300°C	300/500V	NIKEL	
C037	im:6	TSVR-Ni			250°C	300/300V	NIKEL	
C038	im:5	TSVVR Several Variants			270°C	300/500V	COPPER FLEXIBLE	Class 5

7 - 010 SINGLE CORE CABLES-SPECIAL CONSTR.

Spec.		Product Name		CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C034	im:6	TS Several Variants				250°C	300/500V	COPPER FLEXIBLE	Class 5
C035	im:5	TS/Ni				250°C	300/500V	NIKEL	
C300	im:3	VH - RR - FRENI				250°C	48V	COPPER FLEXIBLE	Class 5
C301	im:6	FT2G4T2				200°C	48V	COPPER FLEXIBLE	Class 5

8 - 006 VARIOUS CABLES WITH PVC INSULATION

Spec.		Product Name		CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C261	im:10	FRDR - FR 300/500 - FR3 HT				70°C	300/500V	COPPER FLEXIBLE	Class 5
C262	im:5	FROR CC				70°C	300/500V	COPPER FLEXIBLE	Class 5

9 - 011 MULTICORE SILICONE/SILICONE CABLES

Spec.		Product Name		CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C023	im:21	FG4OG4/2 Several Variants with or without armou	*(SIHF)*			180°C	300/500V	COPPER FLEXIBLE	Class 5
CA23	im:3	FG4OG4/2 S - Several Variants with shielding				180°C	300/500V	COPPER FLEXIBLE	Class 5
CB23	im:1	FG4OG4/2 G-T200 FG4OG4/2 X-T200 FG4OG4/2 CC-T200				200°C	300/500V	COPPER FLEXIBLE	Class 5
C024	im:13	FG4OG4T2/2 Several Variants	*(SiHF/GL)*			200°C	300/500V	COPPER FLEXIBLE	Class 5
C028	im:11	FG4W 180 or 250°C	*(SIFZ-w)*			250°C	300/300V	COPPER FLEXIBLE	Class 5
CA28	im:2	UG4W	*(SIDZ-w)*			180°C	300/500V	COPPER SOLID	Class 1
C029	im:7	FG4WT2-THT/Ni				250°C	300/300V	NIKEL	
C303	im:14	SIHF G				180°C	300/500V	COPPER FLEXIBLE	Class 5
C063	im:16	H05SS-F Several Variants				180°C	300/500V	COPPER FLEXIBLE	Class 5
CA63	im:10	H05SSD3-K H05SSD3T-K Several Variants				180°C	300/500V	COPPER FLEXIBLE	Class 5
CB63	im:6	H05SS-F G (VM)				180°C	300/500V	COPPER EXTRA-FLEX.	Class 6
CA64	im:6	UG4OG4 Several Variants				180°C	300/500V	COPPER SOLID	Class 1
C175	im:1	cUL MULTICONDUCTOR CABLE 150-300				150°C	300V	COPPER FLEXIBLE	UL Standard
C176	im:0	cUL MULTICONDUCTOR CABLE 200-300				200°C	300V	COPPER FLEXIBLE	UL Standard
C451	im:4	UL Style 4389 150-600				150°C	600V	COPPER FLEXIBLE	UL Standard
C452	im:3	UL Style 4389 200-600				200°C	600V	COPPER FLEXIBLE	UL Standard

10 - 012 MULTICORE SILICONE/PVC CABLES

Spec.		Product Name		CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C302	im:7	EI2-SiF-PV/P(fl)				90°C	48V	COPPER FLEXIBLE	Class 5
C305	im:5	EI2-SiF-PV/P(E)				90°C	48V	COPPER FLEXIBLE	Class 5
C304	im:8	SIHF-PV G				90°C	300/500V	COPPER FLEXIBLE	Class 5
C054	im:20	FG4OR Several Variants				90°C	300/500V	COPPER FLEXIBLE	Class 5

CA54	im:5	FG4ORY Several Variants	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
C061	im:14	FG4DR	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5
C064	im:10	UG4OR Several Variants	CE		90°C	300/500V	COPPER SOLID	Class 1
C082	im:16	SiMHYW Several Variants	CE		90°C	300/500V	COPPER FLEXIBLE	Class 5

11 - 015 MULTICORE CABLES-SPECIAL CONSTR.

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C019	im:16	VHO–A Several Variants	CE		250°C	300/300V	COPPER FLEXIBLE	Class 5
CA19	im:1	VHTO-A R.Ni	CE		270°C	300/500V	---	
C025	im:10	FG4OT2/2 G	CE		200°C	300/300V	COPPER FLEXIBLE	Class 5
C313	im:1	FG4OG4/2-PS (SiHF/C)	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5

12 - 022 MULTICORE CABLE WITH HELICOIDAL ASSEMBLY

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C308	im:0	PVC D.I./RY - PVC D.I./PE	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5
C309	im:1	PVC/RY - PVC/PE	CE		70°C	300/500V	COPPER FLEXIBLE	Class 5
C310	im:3	FG4TX/2-RY FG4TX/2-PE	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
C311	im:2	FG4T2X/2-RY	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5
C312	im:0	FG4TX D.I. - PE	CE		180°C	300/500V	COPPER FLEXIBLE	Class 5

13 - 016 SPECIAL PRODUCTS

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C026	im:14	SVFR			500°C		IRON-ALLUMINIUM-INOX etc.
C027	im:9	CORDONETTI			200°C		SUPPORT

14 - 017 THERMOREGOLATION CABLES

Spec.		Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type	
C221	im:6	FRDR-T			70°C	48V	ALLOY	
C222	im:7	FRDR-TA			70°C	48V	ALLOY	
C223	im:6	FROPSR-T			70°C	48V	ALLOY	
C224	im:7	FROASR-T			70°C	48V	ALLOY	
C225	im:4	FROR-TA			70°C	48V	ALLOY	
C226	im:5	FROR-T			70°C	48V	ALLOY	
C231	im:21	VHDT2 Several Variants			250°C	48V	ALLOY	
C232	im:16	VHOT2-T Several Variants			250°C	48V	ALLOY	
C233	im:14	VHOT2-TR Several Variants	*(PT 100)*		250°C	48V	COPPER FLEXIBLE	Class 5
C241	im:8	FG5O-TS UG5O-TS			250°C	48V	ALLOY	
C251	im:11	FG4OG4-T			180°C	48V	ALLOY	
C252	im:5	FG4OG4-TA			180°C	48V	ALLOY	
C253	im:8	FG4OASG4-T			180°C	48V	ALLOY	
C254	im:8	FG4OG4-TS			180°C	48V	ALLOY	

15 - 018 PROTECTION AND INSULATION SLEEVES

Spec.	Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C101 im:9	G.801			250°C		---
C102 im:11	G.810/N - G.830/SIL - G.840/SIL/CAR			180°C		---
C103 im:9	G.600			180°C		---
C105 im:7	G810/S			250°C		---
C106 im:3	G.810/R			250°C		---
C107 im:1	G.600R			150°C		---
C104 im:13	TS1801 (kV 1,50 - 2,50 - 4,00)			200°C		---

16 - 031 MONOTUBES FOR STEAM IRON SYSTEMS

Spec.	Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C801 im:8	MONOTUBO con cavo VDE SIL/PVC	CE		90°C	300/300V	COPPER FLEXIBLE Class 5
C805 im:9	MONOTUBO con cavo HAR SILICONE	CE		180°C	300/500V	COPPER FLEXIBLE Class 5
C806 im:3	MONOTUBO con cavo SPECIALE SILICONE	CE		180°C	300/300V	COPPER EXTRA-FLEX. Class 6
C815 im:8	MONOTUBO con cavo HAR H05RR-F o H05BB-F	CE		90°C	300/500V	---

17 - 030 STEAM TUBES

Spec.	Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C851 im:9	Tubo EPDM RIVESTITO	CE		130°C		---
C852 im:5	Tubo EPDM	CE		130°C		---
C853 im:1	Tubo SILICONE NON RIVESTITO	CE		250°C		---

32 - S14 VARIOUS CABLES WITH PVC INSULATION

Spec.	Product Name	CE UKCA	Homolog.	Temperature Range (°C)	Working Voltage	Conductor Type
C307 im:0	B03VV-F-T/RY - B03VV-F-T/PE	CE		70°C	300/300V	COPPER FLEXIBLE Class 5